


LH-302

General Description

The LH-302 headset is a dual-sided lightweight headset for the ultimate in daylong comfort. Offering a noise-canceling microphone with a semi-rigid, fully adjustable boom for precise positioning. The high-quality wide band dynamic earphones are covered in a pliable material for better fit, isolation and frequency response.

Features

- Fully rotating boom microphone positionable for right- or left-side use
- Boom mounted, noise-canceling electret microphone
- Soft, pliable ear cushions and headband pads



LH-302 Reference View

Order Information

Models

- LH-302-DM-A4F • Double Side, Dynamic Mic, A4F
- LH-302-DM-A4M • Double Side, Dynamic Mic, A4M
- LH-302-DM-A5F • Double Side, Dynamic Mic A5F
- LH-302-DM-A5M • Double Side, Dynamic Mic, A5M
- LH-302-EM-i3.5 • Double Side, Electret Mic, 3.5mm
- LH-302-DM-PT • Double Side, Dynamic Mic, PT
- LH-302L-6.3 • Double Side Headphone, No Mic, 6.3

Accessories

- LH-WS • Windscreen for LH Series 2 pcs
- LH-EC1 • Foam Ear Cushion for LH Series 2 pcs
- LH-EC2 • Supple Ear Cushion for LH Series 2 pcs
- LH-CC • Clothing Clip for LH Series
- LH-SC • Storage Case for LH Series
- LH-HBP • Headband Pad for LH Series
- LH-HC • Hygiene Covers for LH Series 10 pcs

For ordering information, contact your regional sales representative at www.rtsintercoms.com

Specifications

The specification information is subject to change without notification.

Headphones

Type:

Dynamic

Impedance:

150 Ω ±20% @1kHz -

- LH-302-DM-A4F
- LH-302-DM-A4M

300 Ω ± 20% @1kHz -

- LH-302-DM-A5F
- LH-302-DM-A5M
- LH-302-DM-PT
- LH-302-EM-i3.5

Frequency Response:

200Hz – 10 kHz (-10 dB re. 1 kHz)

Sensitivity:

98 ± 4 dB SPL @ 1kHz & 1 mW with B&K 4153 (150 Ω)
100 ± 4 dB SPL @ 1kHz & 1 mW with B&K 4153 (300 Ω)

Microphone

Element Type:

Noise-Canceling Dynamic -

- LH-302-DM-A4F
- LH-302-DM-A4M
- LH-302-DM-A5M
- LH-302-DM-PT

Noise-Canceling Electret

- LH-300-EM-i3.5

Impedance:

Dynamic: 200 Ω
Electret; approx. 2.2 kΩ

Frequency Response:

Dynamic

200 Hz – 6500 Hz

Electret

200 Hz – 10 kHz

Sensitivity:

Dynamic

-63 ± 3.5dB re: 1 V/Pa @ 1 kHz

Electret

-41 ± 3.5dB re: 1 V/Pa @ 1 kHz

Operating Voltage:

Electret Microphone

2V through 2.2K resistor

Connector Type:

LH-302-DM-A4F

4-pin female XLR

LH-302-DM-A4M

4-pin male XLR

LH-302-DM-A5F

5-pin female XLR

LH-302-DM-A5M

5-pin male XLR

LH-302-DM-PT

no connector

LH-302L-6.3

2 conductor 6.3mm

LH-302-EM-i3.5

4 conductor 3.5mm

Physical Weight:

headset weight

wearing weight

with cord

(without cord)

LH-302-DM-A4F

~6 oz (~170 g)

~3.4 oz (~96 g)

LH-302-DM-A4M

~6 oz (~170 g)

~3.4 oz (~96 g)

LH-302-DM-A5F

~6 oz (~170 g)

~3.4 oz (~96 g)

LH-302-DM-A5M

~6 oz (~170 g)

~3.4 oz (~96 g)

LH-302-DM-PT

~4.7 oz (~133 g)

~3.4 oz (~96 g)

LH-302-EM-i3.5

~4.2 oz (~119 g)

~3.4 oz (~96 g)

LH-302L-6.3

~3.8 oz (~108 g)

~2.9 oz (~82 g)

Cord Length:

6 ft. ± 4 in. (1.8m ± 10.0 cm.) (measured from tip to the earshell)

Color:

Black and Stainless Steel

Available Connector Types

LH-302-DM-A4M – 4-pin Male XLR



LH-302-DM-A4F – 4-pin Female XLR



LH-302-DM-A5M – 5-pin Male XLR




LH-302L-6.3


2 Conductor 6.3



LH-302-DM-A5F – 5-pin female XLR



LH-302-EM-i3.5 – 4 Conductor 3.5mm



LH-302-DM-PT –

The pigtail version comes with no connector. It is the customer's responsibility to install the proper connector

Pigtail Wiring Color Codes

Microphone +: White

Microphone -: Blue

Microphone Shield: Inner Shield

Boom Side Speaker +: Yellow

Non-Boom Side Speaker +: Red

Speaker -: Black

Speaker Shield: Outer Shield

Example Headband

