

17" RACK MOUNT LCD MONITOR



- 17" LCD display (1280 x 1024 resolution) in 7U (12.25") of rack space.
- Fast video response time for sharp text and crisp motion.
- 1000:1 Static contrast ratio provides superior detail.
- Optional Lexan™ (L) or 5 wire resistive touchscreen (T).
- Optional NTSC Composite Video and S-Video inputs (V) .



GENERAL SPECIFICATIONS

Dimensions:

19.0" (W) x 12.3" (H) x 1.75" (D)

Weight:

9.5 lbs.

Power:

110 - 240 VAC, 50/60 Hz.
60 Watts max.

Plug & Play:

DDC1 and DDC2B

Temperature:

Operating: 0°C to 50°C
Storage: -20°C to 60°C

Humidity:

Operating: 10 to 90% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

Input Signal (Digital):

DVI-D (TDMS).

Input Connectors:

Analog: 15-pin mini D-Sub.
Digital: 24 pin DVI-D.

Colors Available:

Light Gray or Black (B).

Compatibility:

PC/Windows, Macintosh.

Colors Available:

Black.

DISPLAY SPECIFICATIONS

Display Type:

TFT active matrix LCD.

Viewable Size:

17.0" diagonal.

Colors Displayed:

16.7 million colors.

Contrast Ratio :

1000:1.

Brightness:

250 cd/m² typ.

Viewing Angles:

170°/160° H/V.

Response Time:

5 ms Typ.

Optimum Resolution

1280 x 1024..

Light Source:

Long Life (50,000 hrs typ).

Panel Surface:

Anti-glare.

Specifications subject to change without notice.

MODEL NUMBER

RMM-917/XX

Blank = Standard Screen.

L = Lexan™ Screen Protection.

T = 5 Wire Resistive Touch Screen.

Blank = ARGB and DVI-D Inputs.

V = Composite NTSC, S-Video, ARGB and DVI-D Inputs.

Offering OEM and custom solutions.
Contact us for additional information.



RECORTEC, INC.

www.recortec.com

sales@recortec.com

1-800-729-7654

3329 Kifer Road
Santa Clara, CA 95051

Tel: 408-928-1480
Fax: 408-928-1489