



## evolution wireless G4 SR IEM G4 | Stereo Transmitter



Half-rack stereo transmitter in a full-metal housing with OLED display for full control delivering clarity along the whole frequency spectrum for daily use on stage with evolution wireless G4 In Ear Monitoring systems.

### FEATURES

- Half-rack stereo transmitter in a full-metal housing with OLED display for full control
- Easy and flexible wireless synchronization between transmitter and receiver via infrared
- Compatible with Sennheiser WSM control software for flexible frequency allocation
- Up to 16 compatible channels
- Up to 42 MHz bandwidth with 1680 selectable frequencies, fully tunable in a stable UHF range
- Transmission Range: up to 100 meters / 300 feet
- High RF output power (up to 50 mW) depending on country regulations

### DELIVERY INCLUDES

- SR IEM G4 stereo transmitter
- rod antenna
- power supply
- GA 3 rackmount set
- quick guide
- safety guide
- manufacturer declaration sheet

### PRODUCT VARIANTS

#### Made in Germany

<b>SR IEM G4-A1</b>	470 - 516 MHz	Art. no. 507842
<b>SR IEM G4-A</b>	516 - 558 MHz	Art. no. 507843
<b>SR IEM G4-GB</b>	606 - 648 MHz	Art. no. 507844
<b>SR IEM G4-G</b>	566 - 608 MHz	Art. no. 507845
<b>SR IEM G4-B</b>	626 - 668 MHz	Art. no. 507846
<b>SR IEM G4-C</b>	734 - 776 MHz	Art. no. 507847
<b>SR IEM G4-E</b>	823 - 865 MHz	Art. no. 507848

#### Assembled in USA

<b>SR IEM G4-A1</b>	470 - 516 MHz	Art. no. 508181
<b>SR IEM G4-A</b>	516 - 558 MHz	Art. no. 508182
<b>SR IEM G4-AS</b>	520 - 558 MHz	Art. no. 508183
<b>SR IEM G4-G</b>	566 - 608 MHz	Art. no. 508184
<b>SR IEM G4-B</b>	626 - 668 MHz	Art. no. 508185
<b>SR IEM G4-C</b>	734 - 776 MHz	Art. no. 508186
<b>SR IEM G4-D</b>	780 - 822 MHz	Art. no. 508187



# evolution wireless G4

## SR IEM G4 | Stereo Transmitter

### SPECIFICATIONS

RF characteristics	
Modulation	Wideband FM stereo (MPX pilot tone)
Frequency ranges	A1: 470 - 516 MHz A: 516 - 558 MHz AS: 520 - 558 MHz G: 566 - 608 MHz GB: 606 - 648 MHz B: 626 - 668 MHz C: 734 - 776 MHz D: 780 - 822 MHz E: 823 - 865 MHz
Transmitting frequencies	Max. 1680 frequencies, adjustable in 25 kHz steps  20 frequency banks, each with up to 16 factory-preset channels, no intermodulation  6 frequency banks with up to 16 programmable channels
Switching bandwidth	up to 42 MHz
Nominal/peak deviation	±24 kHz / ±48 kHz
MPX pilot tone (frequency/deviation)	19 kHz/±5 kHz
Frequency stability	±10 ppm
Antenna output	BNC socket, 50 Ω

RF output power at 50 Ω	switchable: Low: typ. 10 mW Standard: typ. 30 mW High: typ. 50 mW
-------------------------	--

AF characteristics	
Compander system	Sennheiser HDX
AF frequency response	25 Hz to 15 kHz
AF input BAL AF IN L (I) + MONO/ BAL AF IN R (II)	2x XLR-3/¼" (6.3 mm) jack combo socket, electronically balanced
Max. input level	+22 dBu
Total harmonic distortion (THD)	<0.9 %
Signal-to-noise ratio (at nominal load and peak deviation)	>90 dB
AF output LOOP OUT BAL L (I)/ LOOP OUT BAL R (II)	¼" (6.3 mm) stereo jack socket, balanced

Overall device	
Temperature range	-10 °C to +55 °C
Power supply	12 V DC
Current consumption	max. 350 mA
Dimensions	Approx. 202 x 212 x 43 mm
Weight	Approx. 980 g

### CONNECTIONS






# evolution wireless G4

## SR IEM G4 | Stereo Transmitter

### DIMENSIONS





# evolution wireless G4

## SR IEM G4 | Stereo Transmitter

### ARCHITECT'S SPECIFICATION

The wireless stereo rack-mount transmitter shall be for use with a companion receiver as part of a wireless RF monitoring system.

The transmitter shall operate within nine UHF frequency ranges, with a switching bandwidth of up to 42 MHz: 470 – 516 MHz, 516 – 558 MHz, 520 – 558 MHz, 626 – 668 MHz, 734 – 776 MHz, 780 – 822 MHz, 823 – 865 MHz, 566 – 608 MHz, 606 – 648 MHz; transmitting frequencies shall be 1,680 per range and shall be tunable in 25 kHz steps. The transmitter shall feature 20 fixed frequency banks with up to 16 compatible frequency presets and 6 user banks with up to 16 user programmable frequencies.

The transmitter shall be menu-driven with a backlit OLED display showing the current frequency, frequency bank and channel number, metering of AF level, transmission status, transmission power, equalizer setting, input sensitivity, and lock status. An auto-lock feature shall be provided to prevent settings from being accidentally altered.

The parameters of associated receivers shall be configurable in the transmitter menu and synchronized with the receivers via an integrated infrared interface.

Frequency stability shall be  $\pm 10$  ppm. RF output power at 50  $\Omega$  shall be switchable between 10 mW (low), 30 mW (standard) and 50 mW (high).

The stereo audio input shall utilize two discrete (left/right) electronically balanced  $\frac{1}{4}$ " (6.3 mm) jack/XLR-3F combo sockets; the audio output shall utilize a balanced  $\frac{1}{4}$ " (6.3 mm) jack socket; an audio loop output shall be provided utilizing two balanced  $\frac{1}{4}$ " (6.3 mm) jack sockets. A headphone output with headphone volume control shall be provided and shall utilize a  $\frac{1}{4}$ " (6.3 mm) stereo jack socket. The transmitter shall have an Ethernet port (RJ-45) for remote network-based monitoring and control using the Sennheiser Wireless System Manager software. One 50  $\Omega$  BNC-type input socket shall be provided for connecting the antenna.

Nominal/peak deviation shall be  $\pm 24$  kHz/ $\pm 48$  kHz. The transmitter shall incorporate the Sennheiser HDX compander system and shall include a 19-kHz MPX pilot tone with a  $\pm 5$  kHz deviation. The audio frequency response shall range from 25 – 15,000 Hz. Maximum input level shall be +22 dBu. Total harmonic distortion (THD) at 1 mV and nominal deviation shall be  $< 0.9$  %. Signal-to-noise ratio at nominal load and peak deviation shall be  $> 90$  dB.

The transmitter shall operate on 12 V power supplied from the NT 2-3 mains unit (for 100 – 240 V AC, 50/60 Hz). Power consumption shall be 350 mA. The transmitter shall have a rugged metal housing; dimensions shall be approximately 202 x 212 x 43 mm (7.95" x 8.35" x 1.69"). Weight shall be approximately 980 grams (2.16 lbs). Operating temperature shall range from  $-10$  °C to  $+55$  °C ( $+14$  °F to  $+131$  °F).

The transmitter shall be the Sennheiser SR IEM G4.