

Gigabit Fiber SFP Transceiver - Cisco GLC-LH-SMD Compatible - SM/MM LC - 10km - TAA Compliant

Product ID: GLCLHSMDDTTA



This StarTech.com Gigabit fiber SFP is a TAA compliant transceiver module, equivalent to the Cisco GLC-LH-SMD SFP. engineered to deliver reliable network connections. Built to exacting specifications and fully tested to ensure maximum performance, this high-quality fiber transceiver module can be installed into Cisco® switches and routers that support the GLC-LH-SMD transceiver module, as well as other major brands of networking equipment.

It provides a dependable and cost-effective way to add, replace or upgrade the ports on your 1000Base-LX/LH networking equipment, and it's backed by a lifetime warranty.

TAA compliant, built for reliable performance

This TAA compliant product adheres to the requirements of the US Federal Trade Agreements Act (TAA), allowing government GSA Schedule purchases.

Engineered to deliver reliable network connections, this single-mode/multimode SFP transceiver is manufactured by StarTech.com to meet or exceed OEM specifications and comply with the industry's MSA (Multi-Source Agreement) standards. Committed to the highest standards of quality, StarTech.com provides an extensive range of networking products including copper and fiber network cards, fiber media converters, Ethernet switches and wireless products.

Fully compatible with Cisco and other major brands

The SM/MM Gigabit SFP is engineered to the highest quality standards and is 100% Cisco compatible, equivalent to the Cisco GLC-LH-SMD SFP transceiver. The StarTech.com SFP transceiver is configured and fully tested to ensure it works seamlessly with Cisco or other major brands of networking equipment.

You can be assured that the use of StarTech.com SFP products should not affect the warranty protection of your networking equipment.

Convenient and scalable

Delivering both convenience and scalability, this fiber transceiver is fully hot-pluggable, which enables you to install it without interrupting network traffic or having to reboot your equipment. It provides a versatile and cost-effective solution that's compatible with a wide range of Gigabit networking devices.

Ideal for use in switches, routers and other networking equipment, the SFP provides reliable performance, enabling you to expand your network to remote segments cost-effectively. The SFP supports Digital Diagnostics Monitoring and both single-mode (with maximum distance of 10 km or 6.2 mi.) and multimode (with a maximum distance of 550 m or 1804 ft.). It provides maximum data rates of up to 1.25Gbps.

You can count on GLCLHSMDSTTA for reliable performance, backed by a lifetime warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- TAA compliant, allowing government GSA Schedule purchases
- Replace defective or damaged SFPs in MSA compliant or Cisco equipment
- Ideal for deployment in network devices with multiple SFP slots
- Expand your network to remote segments

Features

- TAA compliant
- Delivers reliable Gigabit Ethernet connections for 1000Base-LX/LH compliant networks
- 100% Cisco compatible SFP, equivalent to GLC-LH-SMD
- Backed by lifetime warranty and free lifetime technical support
- Meets or exceeds OEM specifications and MSA (Multi-Source Agreement) industry standards
- Supports Digital Diagnostics Monitoring (DDM / DOM)
- 1310 nm optical wavelength
- Supports single-mode (maximum distance 10 km / 6.2 mi.) and multimode (maximum distance 550 m / 1804 ft.)
- LC fiber connector
- Maximum data rates up to 1.25Gbps
- Hot-pluggable

| | | |
|-------------------------------------|-------------------------------|--|
| Hardware | Warranty | Lifetime |
| | Compatible Brand | Cisco |
| | Industry Standards | IEEE 802.3z 1000BASE-LX/LH |
| Performance | Auto MDIX | Yes |
| | Compatible Networks | 1000 Mbps (1 Gbps) |
| | DDM | Yes |
| | Fiber Operating Mode | Full-Duplex |
| | Fiber Type | Single Mode / Multi Mode |
| | Max Transfer Distance | 10 km (6.2 mi) |
| | Maximum Data Transfer Rate | 1.25 Gbps |
| | MTBF | 807,636 hours |
| | Wavelength | 1310nm |
| Connector(s) | Local Unit Connectors | 1 - Fiber Optic LC Duplex Female |
| Special Notes / Requirements | Note | For use in Gigabit fiber networking equipment and media converters |
| | System and Cable Requirements | MSA or Cisco compliant SFP port |
| Environmental | Humidity | 5~95% RH |
| | Operating Temperature | 0°C to 70°C (32°F to 158°F) |
| | Storage Temperature | -40°C to 85°C (-40°F to 185°F) |
| Physical Characteristics | Color | Silver |
| | Enclosure Type | Zinc-Plated Casing |
| | Product Height | 0.4 in [10.5 mm] |
| | Product Length | 2.2 in [57 mm] |
| | Product Weight | 0.7 oz [19 g] |
| | Product Width | 0.5 in [13.8 mm] |
| Packaging Information | Shipping (Package) Weight | 1.8 oz [52 g] |
| What's in the Box | Included in Package | 1 - SFP transceiver |

Product appearance and specifications are subject to change without notice.