

# Gigabit Fiber SFP Transceiver - Cisco GLC-SX-MMD Compatible - MM LC - TAA Compliant

Product ID: GLCSXMMDSTT



This StarTech.com Gigabit fiber SFP is TAA compliant, equivalent to Cisco GLC-SX-MMD. Built to exacting specifications and fully tested to ensure maximum performance, this high-quality fiber transceiver module can be installed into Cisco® switches and routers that support the GLC-SX-MMD transceiver module, as well as other major brands of networking equipment.

It provides a dependable and cost-effective way to add, replace or upgrade the ports on your 1000Base-SX networking equipment, and it's backed by a lifetime warranty.

## TAA compliant, built for reliable performance

This TAA compliant product adheres to the requirements of the US Federal Trade Agreements Act (TAA), allowing government GSA Schedule purchases.

Engineered to deliver reliable network connections, this multimode SFP transceiver is manufactured by StarTech.com to meet or exceed OEM specifications and comply with the industry's MSA (Multi-Source Agreement) standards. Committed to the highest standards of quality, StarTech.com provides an extensive range of networking products including copper and fiber network cards, fiber media converters, Ethernet switches and wireless products.

### **Fully compatible with Cisco and other major brands**

The SM/MM Gigabit SFP is engineered to the highest quality standards and is 100% Cisco compatible, equivalent to the Cisco GLC-SX-MMD SFP transceiver. The StarTech.com SFP transceiver is configured and fully tested to ensure it works seamlessly with Cisco or other major brands of networking equipment.

You can be assured that the use of StarTech.com SFP products should not affect the warranty protection of your networking equipment.

### **Convenient and scalable**

Delivering both convenience and scalability, this fiber transceiver is fully hot-pluggable, which enables you to install it without interrupting network traffic or having to reboot your equipment. It provides a versatile and cost-effective solution that's compatible with a wide range of Gigabit networking devices.

Ideal for use in switches, routers and other networking equipment, the SFP provides reliable performance that enables you to cost-effectively expand your network to remote segments. The SFP supports Digital Diagnostics Monitoring and works over multimode fiber (with a maximum distance of 550 m / 1804 ft.) and maximum data rates of up to 1.25Gbps.

You can count on GLCSXMMDDSTT for reliable performance, backed by a lifetime warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Replace defective or damaged SFPs in MSA compliant or Cisco equipment
- Ideal for deployment in network devices with multiple SFP slots
- Expand your network to remote segments

### Features

- TAA compliant
- Delivers reliable Gigabit Ethernet connections for 1000Base-SX compliant networks
- Cisco compatible SFP, equivalent to GLC-SX-MMD
- Backed by lifetime warranty and free lifetime technical support
- Meets or exceeds OEM specifications and MSA (Multi-Source Agreement) industry standards
- Supports Digital Diagnostics Monitoring (DDM / DOM)
- 850 nm optical wavelength
- Supports multimode fiber (maximum distance 550 m / 1804 ft.)
- LC fiber connector
- Maximum data rates up to 1.25Gbps
- Hot-pluggable

<b>Hardware</b>	Warranty	Lifetime
	Compatible Brand	Cisco
	Industry Standards	IEEE 802.3z 1000BASE-SX
<b>Performance</b>	Auto MDIX	Yes
	Compatible Networks	1000 Mbps (1 Gbps)
	DDM	Yes
	Fiber Operating Mode	Full-Duplex
	Fiber Type	Multi Mode
	Max Transfer Distance	500 m (1640 ft)
	Maximum Data Transfer Rate	1.25 Gbps
	MTBF	861,479 hours
	Wavelength	850nm
<b>Connector(s)</b>	Local Unit Connectors	1 - Fiber Optic LC Duplex Female
<b>Special Notes / Requirements</b>	<b>Note</b>	For use in Gigabit fiber networking equipment and media converters
	System and Cable Requirements	MSA or Cisco compliant SFP port
<b>Environmental</b>	Humidity	5~90% RH
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-40°C to 85°C (-40°F to 185°F)
<b>Physical Characteristics</b>	Color	Silver
	Enclosure Type	Zinc-Plated Casing
	Product Height	0.4 in [10.5 mm]
	Product Length	2.2 in [57 mm]
	Product Weight	0.7 oz [19 g]
	Product Width	0.5 in [13.8 mm]
<b>Packaging Information</b>	Shipping (Package) Weight	1.8 oz [52 g]
<b>What's in the Box</b>	Included in Package	1 - SFP transceiver

Product appearance and specifications are subject to change without notice.