

## 4 Port VGA Over CAT5 Video Extender - 450ft (150m)

StarTech ID: ST1214T



The ST1214T 4 Port VGA Video Extender over Cat 5 allows a single VGA source to be broadcast to up to four remote displays at distances of up to 500 feet (150 meters). Designed for use with our ST121 VGA Video over Cat 5 extension series of devices, the ST1214T is one of many options designed to help you create a custom VGA distribution and extension solution for many applications including digital signage and video conferencing.

Consisting of the transmitter unit only, this product requires a single [ST121R](#) receiver unit per remote display that you are connecting. If you are looking for an eight port transmitter solution, we offer our [ST1218T](#) 8 port VGA extender unit.

For even more versatility, the [ST121EXT](#) VGA over Cat 5 Repeater can be used to increase the total VGA extension distance by an additional 500 feet(150 meters), allowing the original VGA signal to be broadcast a total distance of 1000 feet (300 meters) from transmitter to receiver. Similarly, up to three repeater units can be used between the transmitter and receiver units allowing a monitor to be connected at each repeater station , while further extending the total distance between the transmitter and receiver units.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Technical Specifications

Warranty	2 Years
Color	Black
Enclosure Type	Aluminum
Product Height	0.8 in [20.6 mm]
Product Length	4.1 in [103 mm]
Product Weight	8.7 oz [246 g]
Product Width	2.5 in [63.9 mm]
Audio	No
Cabling	Cat 5 UTP or better
Daisy-Chain	Yes
Ports	4
Max Distance	150 m / 500 ft
Maximum Analog Resolutions	1600x1200 @ 150ft(50m) 1280x1024 @ 300ft(100m) 1024x768 @ 500ft(150m)
Local Unit Connectors	1 - VGA (15 pin; High Density D-Sub) Male
Local Unit Connectors	2 - VGA (15 pin; High Density D-Sub) Female
Local Unit Connectors	4 - RJ-45 Female
System and Cable Requirements	One <a href="#">ST121R</a> receiver unit per remote display that you are connecting
Center Tip Polarity	Positive
Input Voltage	110 ~ 240 AC
Output Current	0.6A
Output Voltage	9 DC
Power Source	AC Adapter Included
Shipping (Package) Weight	1.4 lb [0.7 kg]
Included in Package	1 - VGA Extender - Transmitter
Included in Package	4 - Rubber Feet
Included in Package	1 - Universal Power Adapter (NA/UK/EU)

Certifications, Reports and Compatibility

