

2 Port High Resolution VGA Video Splitter with Audio - 400 MHz

StarTech ID: ST122PROA



This high resolution VGA splitter offers a practical solution for high-res multi-screen presentations, allowing a VGA video signal as well as the corresponding audio to be broadcast from a computer to up to two sets of VGA monitors and speakers simultaneously.

The VGA splitter is ideal for classrooms, tradeshow, in-store displays or any application where high quality video and audio is required, supporting displays with up to 400 MHz of video bandwidth and high resolution applications up to 2048 x 1536.

To help ensure high quality VGA video even at longer distances, the high resolution VGA splitter features a built-in booster circuit that allows monitors to be located up to 210ft away from the host system.

Designed for simplicity and convenience, the VGA splitter offers easy plug and play installation; a completely hardware-based solution, the VGA splitter requires no software operation, saving both time and hassle.

Backed by our 2-year warranty and free lifetime technical support, this 2-port high-resolution VGA splitter lets you get the most out of your video content with quality construction you can depend on.

Applications

- In-store product merchandising
- Information booths/kiosks
- Trade-shows
- Lecture halls and classrooms
- Airports, bus terminals and train stations

Features

- Compatible with VGA, SVGA and Multisync monitors
- 400 MHz bandwidth provides brilliant 2048 x 1536 resolution
- DDC, DDC2 & DDC2B compatible (on Video Out port 1)
- Includes DC 7.5V power adapter
- Daisy chainable for almost unlimited expansion
- Uses standard monitor extension cables (StarTech.com coaxial VGA cables recommended for best picture quality)

Technical Specifications

Warranty	2 Years
Color	Gray
Product Height	2.8 in [7.2 cm]
Product Length	5.1 in [13 cm]
Product Weight	15.4 oz [437 g]
Product Width	3 in [7.5 cm]
Audio	Yes
Ports	2
Bandwidth	400MHz
Maximum Analog Resolutions	2048x1536 @ 60Hz
Connector A	1 - 3.5 mm Mini-Jack (3 Position) Female
Connector A	1 - VGA (15 pin; High Density D-Sub) Female
Connector B	2 - 3.5 mm Mini-Jack (3 Position) Female
Connector B	2 - VGA (15 pin; High Density D-Sub) Female
Note	Units made before August 2008 shipped with AC 7.5V 800mA power adapter
Input Voltage	120 AC
Output Current	0.6A
Output Voltage	12 DC
Power Source	AC Adapter Included
Shipping (Package) Weight	2.1 lb [1 kg]
Included in Package	1 - 2 Port VGA Splitter
Included in Package	1 - Power Adapter
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

