

## USB PS2 KVM Console Extender Cat5 Extender - 500 ft

*StarTech ID: SV565UTP*



The SV565UTP USB PS2 KVM console extender lets you control a server, computer or multiple computers (connected through KVM switch) over a standard Cat5 or Cat6 UTP network cable connection, at distances of up to 500 ft (150 m) away.

Use your existing keyboard, mouse, and monitor to access both the server room and your office computer, saving space and avoiding the need for a dedicated remote console by allowing you to switch between workstation view and KVM view at the remote location.

For added convenience, the Console/KVM extender supports both USB and PS/2 computer connections, and is compatible with any brand of KVM Switch.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Applications

- Access one or more servers located in a secure server room, from a remote location
- Monitor computer-controlled equipment in a factory or warehouse

**Features**

- Can be used with a single computer or connected to an existing KVM switch
- Easy installation using industry-standard UTP network cable
- Supports a max. extension distance of 500 ft (150 m)
- Supports auto-switching between host and remote users or dedicated control
- Compatible with USB and PS/2 computers at the host and remote locations (PS/2 keyboard and mouse required for remote console)
- Intuitive hotkey commands

**Technical Specifications**

Warranty	2 Years
Color	Black
Product Height	0.8 in [2 cm]
Product Length	3 in [7.5 cm]
Product Weight	10.6 oz [299 g]
Product Width	6.1 in [15.5 cm]
Audio	No
KVM Ports	2
Multi-Monitor	No
PC Interface	USB and PS/2
PC Video Type	VGA
Rack-Mountable	No
IP Control	No
Max Transfer Distance	150 m (492 ft)
Supported Resolutions	1280x1024 @ 300ft/ 100m 1024x768 @ maximum cable length
Console Interface(s)	1 - VGA (15 pin; High Density D-Sub) Female
Console Interface(s)	2 - PS/2 (6 pin; Mini-DIN) Female
Host Connectors	1 - VGA (15 pin; High Density D-Sub) Female
Other Interface(s)	1 - RJ-45 Female
OS Compatibility	OS independent; No software or drivers required
<b>Note</b>	Product weights, measurements and connectors indicate a single unit only (either Host or Remote)
Center Tip Polarity	Positive
Input Current	0.2A
Input Voltage	110 ~ 240 AC
Output Current	0.6A
Output Voltage	9 DC
Plug Type	M
Power Source	AC Adapter Included
Humidity	0~80% RH
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Shipping (Package)	3.5 lb [1.6 kg]

## Weight

Included in Package	1 - Local Unit
Included in Package	1 - Remote Unit
Included in Package	2 - Packs Rubber Feet
Included in Package	2 - Power Adapters
Included in Package	1 - Instruction Manual

## Certifications, Reports and Compatibility

