



NOTES:

1. INSERTION LOSS: 0.25 dB MAX.
2. OPERATION TEMP: -40 °C TO +80 °C.
3. MATERIALS:

ST2 ADAPTER:

- BODY - ZINC ALLOY
- RETENTION WASHER - BRASS, NICKEL PLATED
- SLEEVE - CERAMIC, SINGLE-MODE
- BRASS, MULTI-MODE

DUST CAPS - PVC

- NUT - STEEL, NICKEL PLATED
- LOCKWASHER - STAINLESS STEEL
- FLANGE - ZINC ALLOY

4. THIS PRODUCT IS RoHS COMPLIANT.

PART NUMBER	ST2 ADAPTER SEE NOTE 3	DUST CAP COLOR	FLANGE FINISH
EHST2	SINGLE-MODE	RED	NICKEL
EHST2M	DOUBLE-MODE	BLACK	NICKEL
EHST2B	SINGLE-MODE	RED	BLACK CHROME
EHST2MB	DOUBLE MODE	BLACK	BLACK CHROME

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE 1.5:1		
A	26306	12/1/08	RS	TJK	DATE DRAWN	BY	CHKD	APVD	Switchcraft®
REV	ECO NUMBER	DATE	BY	APVD	5/12/08	JGK	RS 6/2/09	TJK 7/16/09	
REVISIONS					DO NOT SCALE DRAWING				
					NAME			PART No.	
					E SERIES ST2 FIBER OPTIC ADAPTER			EHST2_SERIES	
								REV A	

