

Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA

Telephone: 773.869.1234 www.tripplite.com

4-Port USB Charging Station with OTG Hub - 5V 6A / 30W USB Charger Output

MODEL NUMBER: U280-004-OTG











Description

Tired of searching for wall outlets or swapping out one device to charge another? Tripp Lite's U280-004-OTG Charging hub with OTG is the solution, featuring four ports for charging tablets, phones, or other mobile devices, all at the same time. It provides a single location to charge multiple devices, and its sleek, compact design keeps your charging area neat and clutter free. It features two 5V, 2A ports and two 5V, 1A ports, providing up to 6A for charging the connected devices. Furthermore, it comes with an internal power supply, eliminating the need to fumble around with bulky power adapters. When not being used for charging, it doubles as a USB OTG hub. Simply connect your OTG compatible tablet or phone to the dedicated port on the hub, and then connect up to four USB devices (flash drive, mouse, keyboard, etc.). You can now use those devices on your tablet or phone. So whether you're at home or in the office, our Charging Hub with OTG provides an ideal solution for charging your devices or expanding the functionality of your OTG compatible tablet or phone. Input: 100-240V, 50/60Hz, 1.0A / Output: 5V 6A

Features

- · Features four ports for charging tablets, phones, or other mobile devices in a single location
- Includes two 5V, 2A ports and two 5V, 1A ports
- Doubles as a USB OTG Hub when not being used for charging; connect up to four USB devices (flash drive, mouse, keyboard, etc.) to your OTG compatible tablet or phone
- All four ports are USB Battery Charging (BC) specification v1.2 compliant. Supports iPad; iPhone;
 Samsung Galaxy (Tab, Phone, and Note); Microsoft Surface; and more
- Sleek, compact design keeps charging area neat and clutter free
- Features Over-Temperature and Over-Current detection and protection
- Internal power supply eliminates the need to fumble around with bulky power adapters
- Input: 100-240V, 50/60Hz, 1.0A / Output: 5V 6A
- P059-006 (EU) and P061-006 (UK) power cords (sold separately) available for international use

Highlights

- Charge up to 4 tablets, phones, or other mobile devices
- Features two 5V, 2A ports and two 5V, 1A ports
- Doubles as a USB OTG Hub; connect up to four USB devices (flash drive, mouse, keyboard, etc.) to your OTG compatible tablet or phone
- All four ports are USB Battery
 Charging (BC) specification v1.2
 compliant. Supports iPad;
 iPhone; Samsung Galaxy (Tab,
 Phone, and Note); Microsoft
 Surface: etc.
- Sleek, compact design keeps charging area neat and clutter free
- Input: 100-240V, 50/60Hz, 1.0A
 / Output: 5V 6A

Package Includes

- U280-004-OTG
- Micro-USB OTG Cable 2.6-ft.
- C7 to 1-15P Power Cord 3.9-ft.
- Quick Start Guide



Specifications

•		
OVERVIEW		
UPC Code	037332182937	
ОИТРИТ		
Charging Ports / Amps	(2) 1A; (2) 2A	
Output Capacity	5V 6A	
Charging Method	USB	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
Input Frequency	50/60Hz	
Input Current	120V (0.8A) / 230V (0.4A)	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Blue (Power)	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.20 x 9.50 x 6.00	
Shipping Dimensions (hwd / cm)	5.59 x 24.13 x 15.24	
Shipping Weight (lbs.)	0.90	
Shipping Weight (kg)	0.41	
Unit Packaging Type	Box	
Unit Dimensions (hwd / in.)	1.2 x 4.1 x 3.9	
Unit Dimensions (hwd / cm)	3.05 x 10.414 x 9.91	
Unit Weight (lbs.)	0.45	
Unit Weight (kg)	0.20	
Material of Construction	PC	
Color	White	
ENVIRONMENTAL		
Operating Temperature Range	41 to 95 F (5 to 35 C)	
Storage Temperature Range	-4 to 122 F (-20 to 50 C)	
Relative Humidity	20% to 80% RH, Non-Condensing	
Power Consumption (Watts)	37.7W (Operating) 0.07W (Standby)	





CONNECTIONS		
CONNECTIONS		
Ports	5	
Side A - Connector 1	IEC-320-C8	
Side A - Connector 2	USB A (FEMALE)	
Side B - Connector 1	(4) USB A (FEMALE)	
FEATURES & SPECIFICATIONS		
Technology	USB	
CERTIFICATIONS		
Certifications	Tested to UL 60950-1: 2007, CAN/CSA-C22.2 No. 60950-1:07, IEC 60950-1, EN55022, EN55024, FCC Class B, RoHS	
Approvals	UL Listed	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies