



LED-1002HD2

Two 9.7" rack-mount monitors feature the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on these monitors, and they are the best match for displaying higher resolution megapixel images.

Benefits

- LED backlight: brighter picture using less power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Built-in stereo speakers
- Durable metal case

Related Products

- LED-1002HDL: Flush mount
- LED-1002HDX: Free standing with no front controls
- LED-1002HDLX: Flush mount
- LED-1002HD: Single 9.7" monitor

Specifications

Mount	Rack (5RU)
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	7.8" x 5.9" / 197.6 x 148.8mm
Resolution	1024(H) x 768(V)
Brightness Rating	400 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192 (H) x 0.192 (V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	2ms / 2ms (Rising/Falling)
Audio Power / Speakers	2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
DSP	3D Interlace comb DNR, 4H filter
Dimensions	8.8" x 8.7" x 3" / 223 x 222 x 77mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Power Requirements	12VDC; 2A; Negative Ground
Power Consumption	30 Watts (Max)
Composite	x2 BNC Inputs / Outputs (per monitor)
VGA	x1 15-pin mini D-sub Input (per monitor)
HDMI	x1 Input (per monitor)
Audio	x1 R/L RCA Input
Power	x1 2.1mm DC Input
Weight	Net: 3.75 lbs / 1.7 kg

Specifications subject to change.