



LED-1709HDR

This LED-backlit rack monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

_			•	н
В	en	e	П	Ī

Analog video is very clear with no detail loss

Displays 1080i/p digital video

3D Comb Filter for better picture quality

High contrast ratio for better picture definition

Durable metal case

Related Products

LED-1709HD - 17" LCD monitor with tilting desk stand; wall mountable

LED-1709HDL - 17" LCD monitor in flush-mount

LED-1908HD - 19" LCD monitor with tilting desk stand; wall mountable

LED-1908HDL - 19" LCD monitor in flush-mount for in-wall mounting

LED-1908HDR - 19" LCD monitor in 19" rack-mount

LED-1910HDVB - 19" High Brightness LCD monitor; wall mountable

Specifications	
Mount	Rack (8RU)
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
Native Aspect Ratio	5:4
Visible Screen Size (WH)	13.4" x 10.7" / 340 x 272mm
Resolution	1280(H) x 1024(V)
Brightness Rating	250 cd/m ²
Contrast Ratio	1000:1
Back Light	LED (30K)
Dot Pitch	0.264(H) x 0.264(V)mm
Color Depth	16.7M
Number of Pixels	1,310,720
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	x2 1.5 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
Digital Signal Processor	3D Comb Filter
HDMI	x2 Inputs
Composite	x1 BNC Input; x1 BNC Output
VGA	x1 VGA 15-pin D-sub Input
Audio	x1 L/R RCA Input; x1 3.5 PC stereo Input
Power	x1 2.1mm DC Input
Power Requirements	DC 12V (AC100~240)[50/60]
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Dimensions	8RU x 2.9"
Weight	Net: 11.9 lbs / 5.4 kg; Gross: 17.5 lbs / 8 kg

Specifications subject to change.