



LED-2153HDSDI

This high performance LED-backlit monitor features the latest technology with enhanced picture clarity and sharpness which is ideal for professional broadcast production and HD-SDI video surveillance.

Benefits

- Full HD (1080i/p) with no downscaling
- LED backlight: brighter picture using less power
- Great picture quality with motion adaptive 3D De-Interlacer, digital noise reduction and 4H Comb filter Y/C separation
- HD-SDI Input and Output (Loop-through)
- Durable metal case
- Removable deskstand

Specifications

Mount	VESA 100 x 100mm; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	18.76" x 10.5" / 476.6 x 268.1mm
Resolution	1920(H) x 1080(V) (Full HD)
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (50K)
Dot Pitch	0.24825(H) x 0.24825(V)mm
Color Depth	16.7M
Number of Pixels	2,073,600
Response Time	3.8ms / 1.2ms (Rising/Falling)
Audio Power / Speakers	2 Speakers x 1.5 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Dimensions w/ Deskstand	20.1" x 12.2" x 2.8" / 510 x 310 x 70mm
Dimensions	20.1" x 12.2" x 2.4" / 510 x 310 x 60mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included
Power Consumption	30 Watts (Max) / < 3 Watts (Stand-by)
3GSDI	x1 HD-SDI Input / Output
HDMI	x1 Input
Composite	x2 (BNC) Input / Output
S-Video	x1 Input
Audio	x1 RCA L/R Input; x1 PC Input
Power	x1 2.5mm DC Input
Weight	Net: 12.95 lbs / 5.9 kg

Specifications subject to change.