



## LED-709HD

This versatile, high-definition, LED-backlit monitor is designed primarily for field testing, video production and remote surveillance applications. Multiple mounting options and battery pack options are available.

### Benefits

- LED backlight: brighter picture using less power
- Displays HD signals (1080i/p and 720p)
- 16:9 native aspect ratio
- Built-in 5-wire resistive touch screen
- Battery pack option available for mobility
- IR remote control

### Related Products

- LED-709KIT: monitor, tote bag and BP-563C rechargeable battery
- LED-709HDM: 7" LCD monitor w/ metal case
- LED-709HDML: flush mount w/ metal case
- LED-709HD2: rack mount w/ metal case

### Specifications

<b>Mount</b>	VESA 75 x 75mm; Removable Deskstand
<b>HD Compatible</b>	Yes
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Durable ABS Plastic
<b>IR Remote Control</b>	Yes
<b>Native Aspect Ratio</b>	16:9
<b>Visible Screen Size (WH)</b>	6" x 3.4" / 154.08 x 85.92mm
<b>Resolution</b>	800 x 480
<b>Brightness Rating</b>	250 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	500:1
<b>Back Light</b>	LED (20K)
<b>Dot Pitch</b>	0.0642(H) x 0.1790(V) mm
<b>Number of Pixels</b>	1.2M
<b>Response Time</b>	25ms (Rising/Falling)
<b>Viewing Angle (L/R/T/B)</b>	70/70/50/70 degrees
<b>Dimensions</b>	6.9" x 5.3" x 1.4" / 174 x 134 x 35mm
<b>Operating Temp</b>	-4 ~ 158°F / -20 ~ 70°C
<b>Humidity</b>	90%
<b>Power Requirements</b>	10 VDC to 27 VDC Input; 2A + pin; Negative Ground
<b>Power Consumption</b>	24 Watts (Max)
<b>Touchscreen</b>	x1 USB Output; 5-wire resistive
<b>Composite</b>	x1 RCA and x1 BNC Inputs on cable
<b>VGA</b>	x1 15-pin D-sub Input
<b>HDMI</b>	x1 Input
<b>Audio / Speakers</b>	x2 Speakers; x1 RCA Input on cable
<b>Power</b>	x1 2.1mm DC Input
<b>Weight</b>	Net: 0.75 lbs / 0.34 kg; Gross: 2.85 lbs / 1.3 kg

Specifications subject to change.