



LED-803HD2

Two 8" rack-mount, LED backlit, LCD monitors feature the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on these monitors, and they are the best small screen match for displaying higher resolution megapixel images.

Benefits

- Anti-glare coating provides enhanced display
- LED backlight: brighter picture using less power
- Always-on capability when power is applied
- Multiple source connections
- Built-in speakers
- Durable metal case
- Remote control for easy access

Related Products

LED-803HD

Specifications	
Mount	Rack: 4RU
HD Compatible	Yes
Anti-Glare Coating	Yes
Case	Metal
IR Remote Control	Yes
Native Aspect Ratio	4:3
Visible Screen Size	6.4" x 4.8" / 162 x 121.5mm
Resolution	800(H) x 600(V); displays up to 1080p
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	500:1
Back Light	LED (20K)
PC Compatibility	Yes
Dot Pitch	0.0675(H) x 0.2025(V) mm
Color Depth	16.7M
Number of Pixels	480,000
Response Time	25ms (Rising/Falling)
Audio Power/Speakers	x2 1.5 Watts
Viewing Angle	70/70/50/70 degrees
Dimensions	4RU
Operating Temperature	32 ~ 122°F / -20 ~ 80°C
Humidity	10% ~ 90% RH (Max)
Power Requirements	11.5~13 VDC, 1.2A
Power Consumption	20 Watts (Max)
Composite	x2 BNC Inputs / Outputs
PC	x1 15-pin D-sub Input
HDMI	x1 Input
RS-232	x1 3.5mm Input
Audio	x2 RCA Inputs; x1 3.5mm PC Input
Power	x2 2.1mm DC Input jacks
Weight	Net: 6.1 lbs / 3.05 kg

Specifications subject to change.