

# 1U Rack-Mount Console with 19-in. LCD

MODEL NUMBER: **B021-000-17**



## Description

Tripp Lite's B021-000-17 1U Rackmount Console features an integrated 19" LCD panel, full 88-key keyboard, and touch pad, all in a 1U rackmountable housing. The included KVM cable kit allows for connection to a PS/2 computer or KVM, and a PS/2 to USB adapter is included, which can be used to connect to a USB computer or KVM. The unit features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.. Your peripheral device connects to the USB type A port on the front of the unit, and your computer connects to the USB type A port on the back of the unit using a Tripp Lite [UR020-Series](#) type A M/M cable. Constructed of heavy-duty steel housing.

## Features

- Space savings with 1U 19-inch, rack-mount drawer design
- Features 19-inch LCD TFT active-matrix, color panel
- Features a USB pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Supports resolutions of up to 1366 x 768
- Included PS/2 to USB adapter allows for connection to a USB computer or KVM
- Sleep mode when the monitor cover is closed
- Input 120/240 VAC
- Constructed of heavy-duty steel housing

## Highlights

- Control an entire network in just 1U of rack space; includes keyboard, 19" LCD screen, and touch pad
- Features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Connects to a PS/2 or USB server or KVM switch
- Supports video resolutions up to 1366 x 768
- Rackmountable in 19-inch system rack (1U), from 27" to 42" deep

## Applications

- Use where rack space is at a premium, and where a Server/KVM display is needed.

## System Requirements

- Computer or KVM with a VGA monitor port and USB or PS/2 keyboard/mouse ports

## Package Includes

- 1- B021-000-17 1U Rackmount Console
- 1- KVM Cable Kit ( HD15M to HD15M + 2 PS/2 Male )
- 1-PS/2 to USB Adapter
- 1- C13 to 5-15P Power Cord
- 1- User Manual

# Specifications

| OVERVIEW |   |
|----------|---|
| Users    | 1 |
| INPUT    |   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                     |   |
|-------------------------------------|---|
| Electrical Consumption              | (Line Mode) 30W / (Standby Mode) 5W                                       |
| <b>PHYSICAL</b>                     |   |
| Color                               | Black; Green  |
| <b>ENVIRONMENTAL</b>                |   |
| BTUs                                | (Line Mode) 102 BTU/Hr / (Standby Mode) 17.06 BTU/Hr                      |
| <b>COMMUNICATIONS</b>               |   |
| IP Remote Access                    | No  |
| <b>CONNECTIONS</b>                  |   |
| Connector A                         | HD15 (FEMALE)   |
| Ports                               | 0   |
| PC/Server Connections               | VGA; USB; PS/2  |
| <b>SPECIAL FEATURES</b>             |   |
| Cat5 KVM Switch                     | No  |
| <b>CERTIFICATIONS</b>               |   |
| Certifications                      | UL 60950-1 (USA), CAN/CSA (Canada), FCC Part 15 Class A, CE, IEC 60950-1. |
| NIAP-Certified Secure               | No  |
| <b>WARRANTY</b>                     |   |
| Product Warranty Period (Worldwide) | 1-year limited warranty   |

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>