

2400W 120V Power Conditioner with Automatic Voltage Regulation, 3U Rack-Mount, AC Surge Protection

MODEL NUMBER: **LCR2400**



Description

2400 watt Automatic Voltage Regulation (AVR) system in convenient 3U 19 inch rackmount configuration. Protects sensitive electronics, computer accessories and home theater equipment from power-related damage and performance problems. Extends the useful life of connected equipment by providing optimum voltage conditions for enhanced efficiency and cooler internal operating temperatures. Reliable transformer-based voltage correction circuits maintain 120V nominal output during voltage fluctuations between 89 and 147V. Three levels of voltage stabilization offer targeted response for over-voltages, under-voltages and severe brownouts. Prevents equipment damage and power related performance problems for computer accessories, printers, home theater equipment, a/v components and other sensitive electronic devices. Network-grade AC surge and EMI/RFI noise suppression. Supports loads up to 2400 watts, 20A. Includes 14 AC outlets arranged in two separately filtered banks, 12 ft AC line cord and 7 diagnostic LEDs which display incoming voltage level, surge suppression and line status. \$25,000 [connected equipment insurance](#) (U.S., Canada, and Puerto Rico only).

Features

- Maintains usable 120V nominal output during brownouts as low as 89V and over-voltages as high as 147V
- 2,400 watts output power rating supports heavy 120V loads up to 20 amps
- Convenient rackmount format uses only 3 rack spaces (3U)
- Compatible with 2 or 4 post 19 inch rackmount applications
- Network grade surge suppression
- ISOBAR level surge and noise suppression with two isolated filter banks to prevent noise interaction of connected items
- Complete EMI/RFI noise filtering
- 7 diagnostic LEDs indicate input voltage level
- 14 protected NEMA5-15R output receptacles (2 front/12 rear)
- 12-ft. AC power cord with standard NEMA5-15P input plug
- \$25,000 Ultimate Lifetime [connected equipment insurance](#) (U.S., Canada, and Puerto Rico only)

Highlights

- Automatically adjusts low or high voltage
- 2400 watts continuous
- 14 NEMA 5-15R outlets arranged in two ISOBAR filter banks
- Rackmount cabinet fits standard 19-inch rack enclosures
- \$25,000 [Ultimate Lifetime Insurance](#) (U.S., Canada, and Puerto Rico only)

Applications

- Maintains regulated output voltage during severe brownouts and over-voltages for computer accessories, printers, home theater equipment, a/v components, sound reinforcement, point-of-sale equipment, and other applications requiring clean, regulated AC power.

Package Includes

- LCR2400 Line Conditioner
- Mounting hardware
- Instruction manual



Specifications

OUTPUT	
Nominal Output Voltage(s) Supported	120V
Output Receptacles	(14) 5-15R
Output (Watts)	2400
INPUT	
Input Cord Length (ft.)	12
Input Cord Length (m)	5.40
USER INTERFACE, ALERTS & CONTROLS	
Front Panel LEDs	5 LEDs show incoming voltage status.
SURGE / NOISE SUPPRESSION	
UPS AC Suppression Joule Rating	1440 joules
EMI / RFI AC Noise Suppression	80 dB
PHYSICAL	
Shipping Weight (lbs.)	20.3
Shipping Weight (kg)	9.2
Unit Dimensions (hwd / in.)	5.25 x 19 x 7.75
Unit Dimensions (hwd / cm)	13.34 x 48.26 x 19.7
Material of Construction	Steel
Form Factors Supported	Standard 19 inch rack mount format using 3 rack spaces (3U).
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <http://www.tripplite.com/products/product-certification-agencies>