

# AV Bridge Mini

Audio and Video Encoder

## ORDERING INFORMATION

999-8240-000 - North America

999-8240-001 - Europe/UK

999-8240-009 - Australia/New Zealand

## OVERVIEW

Ideal for lecture capture, conference rooms and video conferencing installations, the AV Bridge Mini makes it simple to encode, capture and stream AV content. With AV Bridge Mini, you can bridge any high-definition HDMI and audio source into soft conferencing applications such as Skype for Business, Zoom and WebEx through the standard USB 3.0 interface. Creating production-quality live streams on platforms like YouTube Live, UStream, LiveStream and Panopto has never been easier with the AV Bridge Mini's flexible RTMP capabilities.

The AV Bridge Mini includes all the features that integrators love about the AV Bridge and AV Bridge Conference, along with some important updates – all in a convenient, smaller half-rack unit size.



## CONNECTOR PANEL

- **Network PoE** – 1 GB Network connection for network, power, control and IP streaming. Midspan Power Injector included
- **USB 3.0** – Uncompressed video output with PCM audio for conferencing applications
- **RS-232** – Control functions of the AV Bridge Mini
- **HDMI IN** – Video from the connected camera
- **AUDIO IN Mic/Line 1 and Mic/Line 2** – Microphone or other audio inputs
- **AUDIO OUT Line 1 and Line 2** – Far end audio from conferencing application or as configured in the audio matrix



## WHAT'S INCLUDED

- AV Bridge Mini
- PoE Power Injector with AC cord set(s)
- 3' (0.9m) cat-5 cable, black
- 6' (1.8m) USB 3.0 cable, type A to B
- 4 qty 3-position phoenix-style connectors
- Rack mounting kit (for mounting the AV Bridge Mini into a full rack space)
- Quick-Start Guide

## FEATURES

- Integrates pro AV sources or systems into software conferencing codec or live streaming applications
- HDMI input accepts 4k (3840x2160) signals and encodes and scales appropriately
- Outputs simultaneous USB 3.0 and IP streaming with up to 1080p quality
- Integrates with external DSPs by providing two balanced audio line inputs and outputs
- Minimizes interoperability problems by implementation of standards-based UVC and UAC drivers

# AV Bridge Mini

## TECHNICAL SPECIFICATIONS

USB 3.0 Type B	Up to 1080p/60
IP Stream	RTSP or RTMP up to 1080p/30
HDMI Input	Audio and video up to 3840x2160
POE	IEEE 802.3af-2003 Standard 15.4W Power and Network Connectivity
RS-232	RS-232 RJ-45 Control Port, 38,400 Baud Rate, Vaddio ASCII Command Protocol
Control	Browser-based user interface for configuration and administration, front panel controls for IP address toggle, power reset, and factory reset, Telnet, and RS-232 for external controllers
Operating/Storage Temperature	0°C to +40°C (32°F to 104°F), 20% to 80% Humidity
Dimensions/Weight	Height 1.72 in (4.4 cm); Width 8.375 in (21.3 cm); Depth 6.0 in (15.2 cm)
Audio Inputs	Stereo USB, Stereo HDMI, and Two Balanced Mic/Line-Level Inputs, Impedance 10Kohm, Phantom Power Available (48 VDC, 10 mA)
Audio Outputs	Stereo USB, AAC IP Audio Stream, and Two Balanced Line-Level Outputs, Impedance < 50 Ohms
Audio I/O Matrix	6x5

Specifications are subject to change without notice.

## BASIC CONNECTION



THE ART OF EASY | vaddio.com  
 131 Cheshire Lane, Suite 500, Minnetonka, MN 55305  
 USA P 800.572.2011 E av.vaddio.support@legrand.com  
 EMEA P +31.495.580.840 E av.emea.sales@legrand.com  
 APAC P +852.2145.4099 E av.asia.sales@legrand.com

A brand of legrand

©2018 Milestone AV Technologies. 180254 10/18 Vaddio is a registered trademark of Milestone AV Technologies. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

Commercial AV Brands Chief | Da-Lite | Middle Atlantic | Projecta | Vaddio