## zylight Me Solar Solar



Variable Color Temperature & Color Correction
Full Color Output for Washes, Highlights & Effects
Built-in DMX & Wireless Control
Passive Cooling - Fanless, Silent Operation
Available with Chimera™ or DoP Choice Softbox
Durable - Versatile - Award Winning



## zylight

## **Color Your World**

Forget the paintbrush. Light your set with the perfect color - even chromakey - blue or green with the wide and soft output of the IS3 and IS3c LED Lights. Zylight's Color Mode produces millions of colors without gels or filters. Find the right color with on-board controls or your iPhone with ZyLink Bridge, and save your favorites with the touch of a button. Or keep it white and bright - both the IS3 amd IS3c are fully dimmable and feature adjustable color temperature and color correction. The "c" originally for Chimera - Soft boxes are now offered from both Chimera or DoP Choice.

R G B A =

## **IS3c Specifications**

| Mechanical  |   |  |  |  |
|-------------|---|--|--|--|
| Size:       | 18.5" x 10.75" x 1.9"   |  |  |  |
| Weight:     | 11 lbs.   |  |  |  |
| Mounting:   | Yoke, Industry-standard mounting plate.                       |  |  |  |
| Electrical  |   |  |  |  |
| Input:      | 48V DC  |  |  |  |
| AC Adapter: | 100-240V, 50-60Hz   |  |  |  |
| Power:      | 220W max.   |  |  |  |
| Output      |   |  |  |  |
| Beam Angle: | 90°   |  |  |  |
| Dimming:    | 0-100%  |  |  |  |
| Presets:    | White Mode - Two: User Defined Color Mode - Two: User Defined |  |  |  |
| LED Life:   | 50,000 Hrs min. before factory recalibration.                 |  |  |  |

----------

Specifications subject to change without notice. The Zylight IS3 is protected by multiple US and Foreign patents with other US and

| Photometric Data | <b>5ft</b><br>1.5m | <b>10ft</b><br>3m | <b>15ft</b><br>4.6m | <b>20ft</b><br>6.1m | <b>25ft</b><br>7.6m |
|------------------|--------------------|-------------------|---------------------|---------------------|---------------------|
|                  |                    |                   |                     |                     | 120°                |
| Dayli            | ght 113 fc         | 26.4 fc           | 11.2 fc             | 6.6 fc              | 4.5 fc              |
| Tung             | sten 123.9 fc      | 29.5 fc           | 12.4 fc             | 7.2 fc              | 4.7 fc              |
| 2                |                    |                   |                     |                     |                     |

Form No. IS3C/1217 Specifications may be subject to change without prior notice. Refer to www.zylight.com for the most current product specifications.

P1

((---

zylight

WHITE

0

COLO